


*= Misura con alimentatore in controsoffitto
Measure with driver in counterceiling



Article code: **4113-4013**

CEILING RECESSED LIGHTING/INCASSO A PLAFONE

Material / Materiale **CRISTALY®**



handmade in Italy



IP20
IP44



C.C.
[m.A.]



Light source / Sorgente luminosa

Type/Tipo	LED
CCT	4000K
Light Source Flux/Flusso Sorgente	3700lm
Power/Potenza	30W
CRI	CRI 85

Installation / Installazione

Type/Tipologia	CEILING RECESSED LIGHTING/ INCASSO A PLAFONE
Weight/Peso	4,9Kg
Insulation class/Classe isolamento	III
IP	IP20/IP44

Accessories & Variants / Accessori & Varianti

All accessories and variants are available on 9010.it.
Tutti gli accessori e le varianti sono disponibili su 9010.it.

Finishes & Colours / Finiture & Colori



CRISTALY® Paintable

Power Supply / Alimentazione

Constant Current/Corrente Costante	700mA
Dimmability/Dimmerazione	AMPLITUDE, PWM (With dimnable driver/Con driver dimmerabile)

See compatible drivers on 9010.it. Multiple modules require a series connection/Vedere driver compatibili su 9010.it. Collegamento moduli multipli in serie

The driver can be placed inside the counterwall or in the counterceiling/Il driver può essere riposto nel controsoffitto o nella controparete

