


GANIMEDE L 230Vac

IP67 IK10 CE   WP    | A A+ A++TIPOLOGIA / *TPOLOGY*Incasso | *Recessed*POSIZIONE INSTALLATIVA | *INSTALLATION POSITION*A parete o a pavimento | *Wall or floor mounting*AMBIENTE INSTALLATIVO | *INSTALLATION LOCATION*Esterno | *Outdoor*

GANIMEDE L

6W

 kg 0,54

GANIMEDE L 230Vac

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

| | |
|---------------------------------------|----------------------------------|
| POTENZA ASSORBITA POWER CONSUMPTION | 6W |
| ALIMENTAZIONE POWER SUPPLY | 230Vac |
| FREQUENZA FREQUENCY | 50/60 Hz |
| ALIMENTATORE POWER SUPPLY UNIT | 230Vac incluso Included |
| COLLEGAMENTO CONNECTION | Tensione di rete Mains voltage |

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

| | |
|---|----------------------------------|
| COLORE LED LED COLOUR | 2700K, 3000K, 4000K |
| INDICE RESA CROMATICA CRI CRI | >80 (2700K, 3000K, 4000K) |
| BINNING | 3 step MacAdam 3 MacAdam steps |
| OTTICHE OPTICS | Diffused |
| FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX | 6W 105lm |
| DURATA MEDIA LED AVERAGE LED LIFE | 50.000h L80 B10 |

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES


| | |
|------------------------------|---|
| PESO WEIGHT | Kg 0,54 |
| FINITURE FINISHES | Vetro Glass |
| INSTALLAZIONE INSTALLATION | A incasso a terra con cassaforma (non inclusa), a incasso su muratura con cassaforma (non inclusa) Recessed on ground with housing box (not included), recessed on brickwork with housing box (not included) |
| MATERIALE MATERIAL | Corpo in alluminio anticorodal, vetro temperato sabbiato Anticorodal aluminium body, tempered sandblasted glass |

CARATTERISTICHE GENERALI | GENERAL FEATURES

| | |
|---|----------------|
| TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE | -10°C +45°C |
| GRADO DI PROTEZIONE INGRESS PROTECTION | IP67 |
| GRADO DI RESISTENZA IMPACT RESISTANCE | IK10 |
| GLOW WIRE TEST GLOW WIRE TEST | 960°C |
| TEMPERATURA SCHERMO SCREEN TEMPERATURE | 40° @ Ta = 25° |
| CLASSE DI ISOLAMENTO APPLIANCE CLASS | I |
| CALPESTABILE WALKOVER | Sì / Yes |
| CARRABILE DRIVE OVER | 2000 Kg |
| SICUREZZA STANDARD STANDARD SAFETY | WP System |
| SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY | GR1 |

GANIMEDE L 230Vac

ACCESSORI | ACCESSORIES

| | |
|-----------------------------|--|
| CODICE / CODE | CAQ62 |
| TIPOLOGIA / TYPOLOGY | Cassaforma Housing box  kg 0,10 |
| MATERIALE MATERIAL | PVC, PLA jig PVC, Dima in PLA |

