

RIVER MINI 24Vdc

IP68 IK08 CE III WP SUB 

TIPOLOGIA / TYPOLOGY


Incasso | Recessed

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A terra, a parete, a immersione | Floor, wall, by immersion mounting

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor



RIVER MINI

2,2W

 kg 0,55

RIVER MINI 24Vdc

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

| | |
|---------------------------------------|---|
| POTENZA ASSORBITA POWER CONSUMPTION | 2,2W |
| ALIMENTAZIONE POWER SUPPLY | 24Vdc |
| ALIMENTATORE POWER SUPPLY UNIT | 24Vdc - 2,2W non incluso not included |
| COLLEGAMENTO CONNECTION | Parallelo Parallel |

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

| | |
|---|--|
| COLORE LED LED COLOUR | 2200K, 2700K, 3000K, 4000K, Red, Green, Blue |
| INDICE RESA CROMATICA CRI CRI | >80 (2200K, 2700K, 3000K, 4000K) |
| BINNING | 3 step MacAdam 3 MacAdam steps |
| OTTICHE OPTICS | 18°, 35°, 57° |
| FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX | 2,2W 102lm 35° |
| DURATA MEDIA LED AVERAGE LED LIFE | 50.000h L80 B10 |

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES


| | |
|------------------------------|--|
| PESO WEIGHT | kg 0,55 |
| FINITURE FINISHES | Acciaio Steel |
| INSTALLAZIONE INSTALLATION | A incasso a terra con cassaforma (non inclusa), a incasso su muratura con cassaforma (non inclusa), installazione fuori dall'acqua con cassaforma standard, installazione in immersione permanente con cassaforma IP68 Recessed on ground with housing box (not included), recessed on brickwork with housing box (not included), installation out of water with standard housing box, permanent immersion installation with IP68 housing box |
| MATERIALE MATERIAL | Corpo in acciaio inox AISI 316L, ghiera in acciaio inox AISI 316L, vetro temperato trasparente e lente in PMMA AISI 316L stainless steel body, AISI 316L stainless steel trim, transparent tempered glass and PMMA lens |


CARATTERISTICHE GENERALI | GENERAL FEATURES



| | |
|---|----------------|
| TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE | -10°C +45°C |
| GRADO DI PROTEZIONE INGRESS PROTECTION | IP68 |
| GRADO DI RESISTENZA IMPACT RESISTANCE | IK08 |
| GLOW WIRE TEST GLOW WIRE TEST | 960°C |
| TEMPERATURA SCHERMO SCREEN TEMPERATURE | 40° @ Ta = 25° |
| CLASSE DI ISOLAMENTO APPLIANCE CLASS | III |
| CALPESTABILE WALKOVER | Sì / Yes |
| CARRABILE DRIVE OVER | 2000 Kg |
| SICUREZZA STANDARD STANDARD SAFETY | WP System |
| SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY | GR1 |

RIVER MINI 24Vdc

ACCESSORI | ACCESSORIES

| | |
|-----------------------------|---|
| CODICE / CODE | CAS20 |
| TIPOLOGIA / TYPOLOGY | Cassaforma Housing box  kg 0,013 |
| MATERIALE MATERIAL | Polipropilene Polypropylene |



| | |
|-----------------------------|--|
| CODICE / CODE | CA821 |
| TIPOLOGIA / TYPOLOGY | Cassaforma IP68 IP68 Housing box   kg 0,07 |
| MATERIALE MATERIAL | PVC |

