



gap X

Design: Klaus Nolting

Lichttechnik:

230V Power LED

2700K

L70/50.000 h

dimmbar über Phasenabschrittdimmer

Installation:

2x Kabeleinführung; Anschlussklemme 3x 1,5 mm²

Material:

Aluminiumguss pulverbeschichtet

+ Sicherheitsglas satiniert

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle

der Energieeffizienzklasse G

Lichtrichtung:

light technology:

230V Power LED

2700K

L70/50.000 h

dimmable via trailing edge dimmer

installation:

2x cable entry point; connection terminal 3x 1,5 mm²

material:

aluminium die-casting powder-coated

+ safety glass satined

protection class: IP65

This product contains a light source of

energy efficiency class G

light direction:

228

125

43

35

Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	91100-27-X-AN	12 W/272 lm
 space grey	91100-27-X-SG	12 W/272 lm
 pure white RAL 9016	91100-27-X-WH	12 W/272 lm
 deep black RAL 9005	91100-27-X-BL	12 W/272 lm

+ verwandte Produkte related products . gap Q . gap Y

Größe in mm
size in mm