www.pvdconcept.be - +32 (0)3 605 77 47 - info@pvdconcept.be - white line . nonalsimply . mirror

pvdconcept*

Nona | Simply Simply short

General

Location:ExteriorClass:CE (Class III)

IP-rating:IP67Driver included:YesInstallation orientation:Wall

Main material: Weathered brass

Dimensions (mm): H: 260mm W: 150mm D: 150mm

Lamp included: Yes (Integral)

Dimmable: No (Dimmable on request)

Models



CODE NNA-020-T20 LED (*)

Simply short weathered brass

120° - 2700K - CRI>90 1xLED 6W - 400lm - 350mA

Required options (*)

NNA-011-TBASE

U-base for installation on paved surfaces

or

NNA-011-TPIC Ground spike for installation in loose ground

www.pvdconcept.be - +32 (0)3 605 77 47 - info@pvdconcept.be - white line . nonalsimply . mirror

pvdconcept°

Nona | Simply Simply short

General

Location: Exterior Class: CE (Class III)

IP-rating:IP67Driver included:YesInstallation orientation:Wall

Main material: Stainless steel 304 powder coated

Dimensions (mm): H: 260mm W: 150mm D: 150mm

Lamp included: Yes (Integral)

Dimmable: No (Dimmable on request)


Models



CODE NNA-020-T20 ALULED (*)


Simply short black

120° - 2700K - CRI>90 1xLED 6W - 400lm - 350mA



Simply short dark bronze

120° - 2700K - CRI>90 1xLED 6W - 400lm - 350mA



NNA-011-TBASE

or

NNA-011-TPIC

U-base for installation on paved surfaces

Ground spike for installation in loose ground